



Global price list

The electrical installation becomes digital.

Valid from June 1st, 2022

All prices listed are average sales prices excluding value added tax.

Reliable and future-proof.



FUSE BOX

Product picture	Description	ASP excl. VAT
	dS-AB150 Starter Kit EASY The Starter Kit EASY contains the most important components for creating a small digitalSTROM Smart Home installation. Can be expanded as required. <u>Content:</u> • 1x dSS20 • 1x dSM20 • 1x dSF20 • 2x GE-TKM300 • 1x SW-TKM200 • 1x GR-KL200 • 1x GE-SDM300-S GTIN/EAN: 7640156794717	EUR 852,00
	dS-BP200 digitalSTROM Basis-Package Fuse Box digitalSTROM basic package fuse box (for 3 circuits). <u>Set contents:</u> • 3 x dSF20 • 3 x dSM20 • 1 x dSS20 GTIN/EAN: 7640156792508	EUR 1.473,00
	dSS20 digitalSTROM Server The digitalSTROM server (dSS) with integrated power supply is available with all digitalSTROM meters (dSM) connected by dS485 bus. • Integration of IP devices (e.g. Sonos, Philips Hue, V-Zug, Logitech Harmony, etc.) and IP-gateways. • Remote access with your smartphone via the digitalSTROM cloud. • Voice control via Google Home and Amazon Alexa. • Hail service bookable in DE and CH. • Server app allow addition features such as timer, send notifications via push and email, etc. • Configuration via the web browser without any additional software. GTIN/EAN: 7640156791747 <u>Further product information</u>	EUR 543,00
	dSS22 digitalSTROM Server 22 REG-Webserver digitalSTROM dSS22 mit integriertem Netzteil für MFH mit Gebäudenetzwerk Breite 36 mm on request GTIN/EAN: 7640156791891	on request

Product picture
Description
ASP excl. VAT

dSM25

digitalSTROM Meter 230 V AC / 50 Hz, 25A

EUR 338,00

The digitalSTROM Meter (dSM) communicates with all digitalSTROM devices and terminals in its circuit. Cross-circuit control is carried out using the dS485 bus. For this, all digitalSTROM meters and an optional digitalSTROM server (dSS) must be connected to each other via a two-wire communication cable.

GTIN/EAN: 7640156792171

[Further product information](#)

dSM20

digitalSTROM Meter 230 V AC, 50 Hz, 16A

EUR 246,00

GTIN/EAN: 7640156791785

[Further product information](#)

dSF20

digitalSTROM Filter 230 V

EUR 64,00

The digitalSTROM Filter (dSF) is used to filter network-side interference and to decouple other installations from the digitalSTROM system. A maximum of three filters are required per sub-distribution, one filter per line conductor (phase).

GTIN/EAN: 7640156791532

[Further product information](#)

dS-FD210

digitalSTROM Filter 16A Device

EUR 129,00

In rare cases, high interference pulses are introduced into the 230 V power supply when operating electrical devices, so that digitalSTROM communication can be impaired. This can be the case, for example, when several switching power supplies are operated simultaneously in close proximity. In such cases, the device filter is installed in front of the interfering device and minimizes the impairment of the grid by high-frequency interference. The dS-FD210 is designed for high-power devices up to 16A such as solar systems, induction stoves. For plug-in devices up to 4A, please use the dS-FD200.

GTIN/EAN: 7640156792843


dS-FD230

Gerätefilter 3x32A

EUR 1.190,00

3-phase filter device 32A for heavy load devices (e.g. solar panel installation, EV-charger,...), 558x378x180 mm

GTIN/EAN: 7640156794724

Product picture**Description****ASP excl. VAT****X-IC-46-0001**

IC DIN-rail Switching Capacity

EUR 183,00

The "dS switching module capacity" in DIN-rail format has been designed to control ventilation devices in the digitalSTROM system. The module is favoured for use in kitchen planning, where the power consumption, e.g. for extractor hoods, is correspondingly higher.

GTIN/EAN: 4260385584601

[Further product information](#)**X-IC-40-0001**

IC DIN-rail Switch-Dim

EUR 159,00

The module is intended for installation in the sub-distribution board, to connect to permanently installed electrical loads such as ceiling or wall luminaires.

GTIN/EAN: 4260385584007

[Further product information](#)**dS-DinClip200**

Mounting clip for DIN-rail

EUR 32,00

Set of 5 pcs, for Din-rail EN 60715 (DE)

The mounting clip is used for mounting other products directly on the Din-rail in the fuse box.

GTIN/EAN: 7640156791617

[Further product information](#)

LIGHT

Product picture	Description	ASP excl. VAT
	GE-TKM300 LIGHT 1-Step Push-button Terminal with Dimmer • Connection for a typical 230 V button dimmer • Output at the terminal • Change brightness in dimmer mode • Switch the connected luminaire on and off via dS commands • Automatic registration of the terminal in the dS system GTIN/EAN: 7640156792768 Further product information	EUR 115,00
	GE-KL200 LIGHT Terminal L Switch Switch 1400W/700VA • For connection of large lamp loads • Built-in behind the button • Connected loads can be controlled via the 230V line via digitalSTROM commands. • Switching also possible without digitalSTROM GTIN/EAN: 4290046000195 Further product information	EUR 123,00
	GE-UMV200 1-10V Universal Module • Control of LED and fluorescent lamp ballasts with analogue dimming input (1..10 V) • 4 output channels • 1 input for one operator button • Complete switching off of the connected devices via switch relay GTIN/EAN: 7640156790603 Further product information	EUR 163,00
	X-IC-48-0001 IC DIM400 module The Smart Home module "IC DIM400" is designed for dimming/switching luminaires in the digitalSTROM network up to 410 Watts / 310 VA / 300 Watts LED. The dSready DIN-Rail module with integrated efficient 300 digitalSTROM technology has a width of 2TE = 36mm. • Switching and dimming of luminaires up to 410W • Mounting in redistributor, width 2HP (36mm) • Automatic registration with the dS-Meter • Status display by LED GTIN/EAN: 4260385584809	EUR 396,00

Product picture	Description	ASP excl. VAT
	GE-SDS200-CW LIGHT Cord Dimmer S, white Switch/Dimmer 150W/105VA • Connection to free-standing luminaires for retrofitting • Installation as supply line for the luminaire • Switch on and off via the 230V line via digitalSTROM commands • Change brightness in dimmer mode • Operation via rocker switch with two buttons, with configurable features GTIN/EAN: 7640156790221 Further product information	EUR 123,00
	GE-SDS200-CS LIGHT Cord dimmer S, black Switch/Dimmer 150W/105VA • Connection to free-standing luminaires for retrofitting • Installation as supply line for the luminaire • Switch on and off via the 230V line via digitalSTROM commands • Change brightness in dimmer mode • Operation via rocker switch with two buttons, with configurable features GTIN/EAN: 7640156790238 Further product information	EUR 123,00
	GE-SDM200 LIGHT Cord Dimmer M Switch/Dimmer 150W/105VA • For connection to free-standing luminaires (floor or table luminaires) • Suitable for retrofitting • Installation in the supply line of the luminaire • Switching on and off via the 230V line via dS commands • Brightness can be changed in dimmer mode While stock lasts. GTIN/EAN: 4290046000034 Further product information	EUR 64,00
	GE-SDM300-S Light cord dimmer M 300 black • For connection to free-standing luminaires (floor or table luminaire) • Suitable for retrofitting • Installation in the supply line of the luminaire • Switching on and off via the 230 V line using dS commands • Brightness can be changed in dimmer mode GTIN/EAN: 7640156794489 Further product information	EUR 117,00
	GE-SDM300-W Light cord dimmer M 300 white • For connection to free-standing luminaires (floor or table luminaire) • Suitable for retrofitting • Installation in the supply line of the luminaire • Switching on and off via the 230 V line using dS commands • Brightness can be changed in dimmer mode GTIN/EAN: 7640156794359 Further product information	EUR 117,00

Product picture**Description****ASP excl. VAT****GE-SDM200-CS**

EUR 74,00

LIGHT Cord dimmer M (Euro plug), black, pluggable

Switch/Dimmer 150W/105VA

- For connection to free-standing luminaires (floor or table luminaires)
- Suitable for retrofitting
- Switching on and off via the 230V line via dS commands
- Brightness can be changed in dimmer mode

While stock lasts.

GTIN/EAN: 7640156791662

Further product information**GE-FD300**

EUR 25,00

digitalSTROM Residual Voltage Filter

Avoids afterglow, flashing or continuous flickering of vulnerable LED/ESL lamps.

GTIN/EAN: 7640156792836

SHADING

Product picture	Description	ASP excl. VAT
	dS-Weather digitalSTROM weather station The weather station measures sensor values for temperature, rain, wind and sunlight, protecting awnings and blinds against wind and rain. • Connection via power line (no additional construction costs) • Sensor values are immediately available after connection • Detailed evaluation of the data • Compatible with other applications GTIN/EAN: 7640156794472 Further product information	EUR 829,00
	GR-KL300 Universal Terminal Block L Open and close your electric shutters, awnings, blinds and curtains easily and conveniently via digitalSTROM commands: The digitalSTROM terminal GR-KL300 allows you to intelligently network different shading types via the 230V line in the digitalSTROM system. • Connection of curtain, roller shutter, awning or blind drives up to max. 700VA(3A). • Up/down function configurable for 1-way and 2-way push-buttons • Shading type freely configurable via software • Allows setting, storage and recall of different shading positions (scenes) • Can be automated for any application scenario (time, presence simulation, etc.) GTIN/EAN: 7640156792782	EUR 135,00
	GR-KL210 SHADE Terminal Block L Blinds • Connection of awning drives with mechanical limit switches • Control of connected loads via the 230V line via digitalSTROM commands • Drive can also be operated via the button without digitalSTROM GTIN/EAN: 4290046000614 Further product information	EUR 109,00
	GR-KL220 SHADE Terminal Block L Venetian Blinds • Connection of lamella blind drives with adjustable lamella angle and two mechanical limit switches • Control of connected loads via the 230V line via digitalSTROM commands • Drive can also be operated via the button without digitalSTROM GTIN/EAN: 4290046000621 Further product information	EUR 109,00

Product picture**Description****ASP excl. VAT****GR-HKL230**

SHADE Relay Terminal Block Venetian Blinds, Hirschmann Plugs

EUR 163,00

- Connection of lamella blind drives with adjustable lamella angle and two mechanical limit switches
- Control of connected loads via the 230V line via digitalSTROM commands

GTIN/EAN: 7640156791587

[Further product information](#)

HEATING / AIR CONDITIONING

Product picture	Description	ASP excl. VAT
	X-TK-1536799 FTW06 LCD dS Gira E2 rws Multifunctional Room Control Unit (Flush-Mounting) 55 x 55mm Frame White matt finish Manufacturer: Thermokon Item number 62480 • Control of ventilation groups • Monitoring and display of the current room temperature and humidity GTIN/EAN: 4251161900067 Further product information	EUR 282,00
	x-TK-619219 Thermokon FTW04 dS Living Room Sensor for Relative Humidity and Temperature (Surface Mounting). Manufacturer: Thermokon Item number 619219 • Monitoring of the current room temperature and humidity • Measured values are automatically made available to the digitalSTROM temperature control system GTIN/EAN: 4251161900036 Further product information	EUR 179,00
	X-TK-1536751 FTW06 dS Gira E2 rws Living Room Sensor for Relative Humidity and Temperature (Flush-Mounting) 55 x 55mm frame White matt finish Manufacturer: Thermokon Item number 624787 • Monitoring of the current room temperature and humidity • Measured values are automatically made available to the digitalSTROM temperature control system GTIN/EAN: 4251161900043 Further product information	EUR 237,00
	X-TK-SR04 EnOcean SR04 Wireless temperature room sensor Manufacturer Thermokon Plastered room sensors with radio to measure temperature in residential and office spaces (Surface Mounting). An EnOcean Gateway is required for commissioning. Further product information	EUR 125,00
	BL-UMV200 digitalSTROM Heating/Ventilation 1-10V controller Control of ventilation units (damper drives, fans, ...) with analogue 0 or 1-10 V input via the 230V line with digitalSTROM commands • 4 output channels • 1 input for an operating push-button • Complete switching off of the connected devices via a switching relay • Switching off the connected consumers via the digitalSTROM system GTIN/EAN: 7640156794687	EUR 163,00

Product picture**Description****ASP excl. VAT****BL-KM200**

HEATING/COOLING Terminal Block M for Thermoelectric Control Valves


EUR 70,00

- For connection of thermoelectric actuators
- The terminal block responds directly to the actuating values of a digitalSTROM installation with individual room temperature control
- Switchable for NC/NO valves

While stock lasts.

GTIN/EAN: 7640156790580

[Further product information](#)

**BL-KM300**

HEATING/COOLING Terminal Block M for Thermoelectric Control Valves

EUR 90,00

- For connection of thermoelectric actuators
- The terminal block responds directly to the actuating values of a digitalSTROM installation with individual room temperature control
- Switchable for NC/NO valves

Follow up product for BL-KM200

GTIN/EAN: 7640156794335

[Further product information](#)

**X-IC-85-0001**

Adapter plug IC BL-ZWD300

EUR 154,00

The digitalSTROM adapter plug IC BL-ZWD300 opens up a wide range of functions for automatic control of the indoor climate - simple, efficient and precise.

- Integrated BL-KM300 technology
- Fully automatic control of electronic heating valves
- Plug & Play system (Schuko and Euro sockets)
- For NO or NC control valves (max. 20W)

GTIN/EAN: 4260385588500

**X-IC-80-0001**

Heating valve module IC BL-300

EUR 159,00

The IC BL-300 heating valve module opens up a wide range of functions for automatic control of the living climate - simple, efficient and precise.

- Integrated BL-KM300 technology
- Fully automatic control of electronic heating valves (switched or PWM)
- Connection for 2 control valves (max. 20W)
- Status LED

GTIN/EAN: 4260385588005

**x-TK-SAB05**

EnOcean SAB05

EUR 150,00

Manufacturer Thermokon
Radio controlled valve actuator for room temperature control.

- Bidirectional communication
- Combines actuator, controller and transmitter

[Further product information](#)

Product picture**Description****X-IC-72-0001**

IC Humidity Detector

Humidity module

The dS Humidity detector module transmits four fixed thresholds 40, 50, 60 and 70% RH humidity to the digitalSTROM system via the connected humidity sensor. The small sensor can be installed in hard-to-reach places, e.g. in the floor or under the roof cladding.

GTIN/EAN: 4260385587206

[Further product information](#)

ASP excl. VAT

EUR 264,00

PUSH-BUTTONS / ADAPTERS

Product picture	Description	ASP excl. VAT
	SW-SKM300 JOKER 4-way Push-button & Sensor Terminal • JOKER 4-way Push-button /Sensor Terminal • Connection of 4 standard 230V buttons or sensors • For buttons from any switch program (light, shading, audio, etc...) GTIN/EAN: 7640156794458 Further product information	EUR 109,00
	X-IC-22-0001 IC T4L-Touch The IC T4L-TOUCH is a capacitive digitalSTROM 4-fold push-button for easy operation of light, shading, music, etc. It is IP66-protected and can be used as a control unit. The IP66 protection class makes it suitable for indoor and outdoor applications. • Capacitive 4-fold push button • 4 individual dSiD's • group selectable: joker, light or shade • IP66 (in- and outdoor) • Pre-programmed and ready for immediate use GTIN/EAN: 4260385582201	EUR 184,00
	X-IC-43-0001 Euro adapter plug IC GE-ZWD300 The IC GE-ZWD300 Euro adapter plug is designed for plug and play connection of consumers to a digitalSTROM Smart Home system. It can be used, for example, to quickly and easily plug movable lights, fairy lights or Christmas lighting into a dS system. • Euro adapter plug • Switching and dimming of luminaires up to 150W • Plug & play connection to a digitalSTROM Smart Home system • Automatic registration of the dS ready product on the dS Meter • Latest digitalSTROM system technology GE-300 GTIN/EAN: 4260385584304	EUR 157,00
	SW-SSL200-FS Cord Switch L (Schuko), black, pluggable • For pluggable connection of large electrical loads • For buttons from any switch program (light, shading, audio, etc.) • Control of the connected loads via the 230V line via digitalSTROM commands GTIN/EAN: 7640156791686 Further product information	EUR 123,00

Product picture
Description
ASP excl. VAT

dS-FD200-FS

Device Filter, black, pluggable

EUR 90,00

In rare cases, high interference pulses enter the 230V network during the operation of electrical devices, which can disrupt digitalSTROM communication. In such cases, the device filter is inserted into the connection cable of the interfering device and the socket outlet and minimises interference to the mains supply.

GTIN/EAN: 7640156791709

[Further product information](#)

X-IC-17-6001

IC T4L-PLUG Modul Low Voltage Button

EUR 183,00

- Module for integrating 4-way buttons into the digitalSTROM system
- Button voltage and external LED supply provided
- Features of the dS terminal SW-TKM 200 Up to 16 functions in the dS system
- Supplied with connection cable, but without upper part of the button (must be ordered separately)

GTIN/EAN: 4260385581761

[Further product information](#)

X-IC-18-4001

IC Push-button T18 (Single Button)

EUR 183,00

- Single button with fully integrated digitalSTROM technology
- Function indicator via internal LED behind the rocker switch
- L and N connected via integrated spring terminals
- Internal design only 5mm deeper than standard

GTIN/EAN: 4260385581846

[Further product information](#)

X-IC-18-0001

IC T18-GE Dimmer Output Button

EUR 183,00

- Contact to the button via high-quality pin contacts
- Easy mounting of the button (due to the flat design) in a simple flush-mounted box
- Connection of the phase L, neutral conductor N lines and L1 of the lamp via integrated spring terminals
- Automatic registration in the circuit distributor

GTIN/EAN: 4260385581815

[Further product information](#)

X-IC-17-4001

IC T4L Push-button Module

EUR 170,00

4-Way Push-button Module

- Integration of extra-low voltage buttons in the dS system
- Features of the SW-TKM 200 dS terminal
- Line voltage of the 4 button inputs via the module
- Installation in flush-mounted box

GTIN/EAN: 4260385581747

[Further product information](#)

X-IC-17-5001

IC T4L-LED Module

EUR 192,00

4-Way/LED Push-button Module

- Integration of extra-low voltage buttons in the dS system
- Particularly suitable for the integration of upper KNX button parts
- Button voltage and external LED supply is provided by the T4L LED

GTIN/EAN: 4260385581754

[Further product information](#)

ROOM CONTROL UNITS

Product picture	Description	ASP excl. VAT
	X-TK-613439 thanos rH S dS white Touch room control unit (flush-mounted) Manufacturer Thermokon Item-no. 613439 thanos rH white dS Elegant control unit for complete and central room control. Easy mounting on the wall in combination with a standard flush-mounted device box. GTIN/EAN: 4251161900029 Further product information	EUR 689,00
	X-TK-613446 thanos rH S dS black Touch room control unit (flush-mounted) Manufacturer Thermokon Item-no. 613446 thanos rH black dS Elegant control unit for complete and central room control. Easy mounting on the wall in combination with a standard flush-mounted device box. GTIN/EAN: 4251161900012 Further product information	EUR 689,00
	X-UL-10230 u::lux Switch dS White Intelligent Room Control Unit with 55 x 55 Design (Flush-Mounted) • Display and operation of room and range buttons • Control of ventilation and room temperature • Display of current weather and temperature data • Option to report faults or alarms acoustically and visually • Switch between day and night mode GTIN/EAN: 747719155903 Further product information	EUR 377,00
	X-UL-10230AB u::lux Switch dS Black Intelligent Room Control Unit with 55 x 55 Design (Flush-Mounted) • Display and operation of room and range buttons • Control of ventilation and room temperature • Display of current weather and temperature data • Option to report faults or alarms acoustically and visually • Switch between day and night mode GTIN/EAN: 747719155958 Further product information	EUR 377,00
	X-UL-10952 u::lux AddOn RH+Temp White Additional module for measuring air humidity and temperature. GTIN/EAN: 747719155538 Further product information	EUR 50,00

Product picture	Description	ASP excl. VAT
	X-UL-10952AB u::lux AddOn RH+Temp Black Additional module for measuring air humidity and temperature. GTIN/EAN: 747719155545 Further product information	EUR 50,00
	X-UL-11092 u::lux AddOn MD+RH+Temp White Additional module for measuring temperature, air humidity & motion sensor. GTIN/EAN: 747719155569 Further product information	EUR 75,00
	X-UL-11092AB u::lux AddOn MD+RH+Temp Black Additional module for measuring temperature, air humidity & motion sensor. GTIN/EAN: 747719155576 Further product information	EUR 75,00
	X-UL-11103 u::lux AddOn CO2+RH+Temp White Additional module for measuring CO2, air humidity & temperature. GTIN/EAN: 747719155620 Further product information	EUR 160,00
	X-UL-11103AB u::lux AddOn CO2+RH+Temp Black Additional module for measuring CO2, air humidity & temperature. GTIN/EAN: 747719155637 Further product information	EUR 160,00
	X-IC-19-5000 IC TLS019 Touch Sensor GTIN/EAN: 4260385581952	EUR 209,00

AUTOMATIZATION

Product picture	Description	ASP excl. VAT
	SW-KL200 JOKER L Terminal Switch 1400W/700VA • Connection of 1-4 different sensors with 230V switching output (e.g. motion detectors, wind and rain sensors) • Sensor states for controlling the loads are transferred to the dS system via the 230V line GTIN/EAN: 4290046000959 Further product information	EUR 123,00
	SW-UMR200 Universal Relay Module • Potential-free capture of mains and low voltage signals (e.g. from bell systems) • Switching of loads • Inputs and 2 potential-free change-over contacts • Input states in the digitalSTROM system for triggering processes GTIN/EAN: 7640156790597 Further product information	EUR 163,00
	X-IC-47-0001 Power module The IC Power digitalSTROM module is a small power pack. With it, the desire for a switchable socket can be realised. • Integrated GE-KM300 technology • Maximum output load: resistive 2875W (12.5A) / inductive 700VA (3A) • Fits even in 45mm flush-mounted box • Status LED GTIN/EAN: 4260385584700	EUR 234,00
	SW-AKM200 JOKER 4-Way Automation Terminal Block • Connection of 1-4 different sensors with 230V switching output (e.g. motion detectors, wind and rain sensors) • Sensor states for controlling the loads are transferred to the dS system via the 230V line While stock lasts. GTIN/EAN: 7640156790405 Further product information	EUR 82,00
	SW-AKM210 JOKER 2-Way Automation Terminal Block • Connection of 1-2 different sensors with 230V switching output (e.g. motion detectors, wind and rain sensors) • Sensor states for controlling the loads are transferred to the dS system via the 230V line GTIN/EAN: 7640156790412 Further product information	EUR 70,00

Product picture**Description****ASP excl. VAT****X-IC-68-0001**

IC BW-HS 300 module

EUR 225,00

The IC BW-HS 300 is a dual function IC Smart Home product with the latest 300 dS technology. The dual sensor is a PIR motion detector with integrated brightness detection.

- Integrated dS 300 technology
- Detection range of motion sensor approx. 180 degrees
- Range 4-7m
- Threshold settings via potentiometer on the rear side
- Noiseless switching process (no click-clack)
- Status LEDs

GTIN/EAN: 4260385586803

**X-IC-60-0001**

IC PIR Sensor

EUR 170,00

Motion detector (55x55mm frame)

- Transmits motion messages directly to the dS system
- Triggering of individual safety functions
- Linking of movement via the APP Scene Responder

GTIN/EAN: 4260385586001

[Further product information](#)**X-IC-64-1001**

IC T12 Plug PIR Euro

EUR 210,00

Plug-in motion detector Schuko version (Euro)

- Transmits motion messages directly to the digitalSTROM system
- Built-in digitalSTROM technology in the connector part
- Can be plugged into another location at any time

GTIN/EAN: 4260385586414

[Further product information](#)**X-IC-78-0001**

IC Brightness Sensor module

EUR 248,00

The IC Brightness Sensor Module was developed for brightness detection for the digitalSTROM system. By means of adjustable potentiometers, two brightness values can be reported directly to the digitalSTROM system as threshold values.

- Integrated SW-AKM210 technology
- 2 potentiometers for threshold value adjustment
- 2 dSiD addresses
- Euro plug

GTIN/EAN: 4260385587800

**X-IC-30-0001**

IC DIN-rail Automatization

EUR 159,00

The module is used for inserting it into the subdistribution and connecting for sensors with switching output (e.g. motion detectors, wind and rain sensors) provided.

- Technical function such as SW-AKM200
- Connection of up to 4 sensors with 230V switching output to the digitalSTROM installation
- Transfers sensor states to the digitalSTROM-system via the 230V powerline
- Led status display

GTIN/EAN: 4260385583000

[Further product information](#)

ACCESS

Product picture	Description	ASP excl. VAT
	X-IC-50-0001 IC DIN-rail Bell Module The module in DIN-rail layout is designed for 2 bell circuits. It processes the incoming 8VAC or 12VAC ring signals and sends them to the digitalSTROM network. GTIN/EAN: 4260385585004 Further product information	EUR 202,00

SECURITY

Product picture	Description	ASP excl. VAT
	X-TK-727297 SRW02 - EnOcean wireless window contact Wireless window contact for status monitoring of windows and doors in connection with the receiver interfaces SRC-x and higher-level monitoring system. Status monitoring of windows and doors. Transmission via wireless telegrams to the receiver in line with EnOcean-standard. Further product information	EUR 100,00
	RT-SDM200 SECURITY Cord Push-Button M Panic • Panic button function (digitalSTROM triggers "alarm" in the house) • Optional: Control of connected signal lamps via the 230V line via digitalSTROM commands GTIN/EAN: 4290046000089 Further product information	EUR 104,00
	X-IC-74-0001 IC Glass Breakage Sensor • Passive piezo sensor • For detection of glass breakage The information is made available to the digitalSTROM system in conjunction with the dS Alarm 400 module. GTIN/EAN: 4260385587404 Further product information	EUR 99,00
	X-IC-70-0001 IC Water Sensor • Notification of faults via the digitalSTROM system via push message (smartphone/email) • Connection to the dS Alarm 400 module GTIN/EAN: 4260385587008 Further product information	EUR 72,00
	X-IC-90-0001 IC Alarm 400 Module The "dS Alarm 400" module is designed to convert up to four low voltage signals to the digitalSTROM system. This enables for example, 4 window contacts, glass breakage or water sensors to be monitored by wire (closed circuit principle). GTIN/EAN: 4260385589002 Further product information	EUR 170,00

GATEWAYS

Product picture	Description	ASP excl. VAT
	x-P44-DSB-E2 Plan44 Gateway EnOcean Manufacturer Part No. P44- DSB-E2 Incl. power supply and LAN cable P44-DSB-E2 expands your digitalSTROM system with push-buttons, sensors and actuators from third-party manufacturers. P44-DSB-E2 uses the new digitalSTROM virtual device connector technology to seamlessly integrate new devices, making them as easy for users to use as normal digitalSTROM components. A single P44-DSB-E2 device connects many wireless pushbuttons, sensors and actuators as well as Philips "hue" colour LED lights. GTIN/EAN: 7640161170056 Further product information	EUR 414,00
	X-P44-DSB-D Plan44 Gateway digitalSTROM-Dali/hue The X-P44-DSB-D digitalSTROM-bridge contains a DALI bus interface and an embedded Linux module with Ethernet. - the digitalSTROM-bridge X-P44-DSB-D is connected via Ethernet to the dS server via the house network (LAN). - the X-P44-DSB-D is automatically recognised by the dS server as a "Virtual digitalSTROM Meter" (vdSM). - Hue light are connected to the X-P44-DSB-D by simply pressing a button. - DALI devices are connected to the 2-wire DALI bus. - all DALI devices connected to the X-P44-DSB-D as well as connected Hue lights automatically appear in the dS system and can be used in the same way as normal dS components. - for further configuration and firmware updates, the web interface of the X-P44-DSB-D can be called up from the dS Configurator via the context menu. GTIN/EAN: 7640161170148 Further product information	EUR 840,00
	X-TK-637442 STC-dS EnOcean receiver/transmitter digitalSTROM The STC-dS Gateway is used to expand a digitalSTROM-system with components, in particular sensors, heating valves and touch switches, which are equipped with EnOcean wireless technology. Connection to the digitalSTROM server is via an Ethernet network connection. GTIN/EAN: 4251161900081 Further product information	EUR 450,00

BOLD SMARTLOCKS

Product picture	Description	ASP excl. VAT
	X-BLD-3530-EUR BOLD Smartlock Cylinder E30I35 Duracore Inside: 30-35 mm Outside: 30-45mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868957	EUR 158,82
	X-BLD-3035-EURB BOLD Smartlock Cylinder E30I35 SX33 Duracore Interiour length: 30mm to 35mm Exteriour length: 30mm to 45mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868018	EUR 167,23
	X-BLD-3045-EURB BOLD Smartlock Cylinder E30I45 SX43 Duracore Interior: 40-45 mm Exterior: 30-45 mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868025	EUR 175,63
	X-BLD-3055-EURC BOLD Smartlock Cylinder E30I55 Duracore Interiour: 50-55 mm Exteriour: 30-45 mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868896	EUR 184,03

Product picture	Description	ASP excl. VAT
	X-BLD-3065-EURC BOLD Smartlock Cylinder E30I65 SX63 Duracore	EUR 192,44
	Interieur: 60-65 mm Extérieur: 30-45 mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868889	
	X-BLD-5035-EURC BOLD Smartlock Cylinder E50I35 SX35 Duracore	EUR 184,03
	Interieur: 30-35 mm Extérieur: 50-65 mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868797	
	X-BLD-5045-EURC BOLD Smartlock Cylinder E50I45 SX45 Duracore	EUR 192,44
	Interieur: 40-45 mm Extérieur: 50-65 mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868780	
	X-BLD-5055-EURC BOLD Smartlock Cylinder E50I55 SX55 Duracore	EUR 200,84
	Innen: 50-55 mm Aussen: 50-65 mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868766	
	X-BLD-5065-EURC BOLD Smartlock Cylinder E50I65 SX65 Duracore	EUR 209,24
	Interieur: 60-65 mm Extérieur: 50-65 mm Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years. GTIN/EAN: 8719992868773	

Product picture**Description****ASP excl. VAT****X-BLD-3035-GWC**

Bundle BOLD Smartlock E30I35 SX33 + Bridge

EUR 234,45

Interior: 30-35 mm

Exterior: 30-45 mm

Set Bold Connect + Bluetooth-connected smart cylinder for easy and secure access without keys. Replaces Euro profile cylinders, easy self-installation, access via smartphone app (iOS, Android) or backup-pin, Bluetooth 4.0 or higher, two-factor authentication and end-to-end data encryption, SKG*** certificate for highest mechanical security, battery life over 2 years.

GTIN/EAN: 8719992868728

**X-BLD-GW-EURB**

BOLD Connect Bridge

EUR 83,19

Bold Connect is an interface to connect your Bold Smart Lock to the internet. Remote activation of your Bold Smart Lock from anywhere using a mobile app. Easy set-up thanks to automatic recognition of the available locks. Possibility to connect several locks to one Bold Connect. End-to-end data encryption on all connected devices.

GTIN/EAN: 8719992868032

FEATURES



With this basic package you can equip your meter cabinet with the basis for your digitalSTROM system. Once installed you can pair the desired devices, lamps and much more with digitalSTROM.

The digitalSTROM Basic Package contains

digitalSTROM Filter	dSF20	3	p.p.	64€
digitalSTROM Meter	dSM20	3	p.p.	246€
digitalSTROM-Server	dSS20	1	p.p.	543€

1.473 €*

The basic package is intended for 3 groups. For each additional group you simply order an extra dSM20 (digitalSTROM Meter).

* VAT excl. and plus shipping costs

The new digitalSTROM App

The perfect App for the perfect Smart Home.

digitalstrom.com/app



For iOS&Android
**The new
digitalSTROM
App!**

CONTROL AND CONFIGURATION

digitalSTROM Smartphone und Tablet Apps

Control and configuration



dS Smart Home
for iOS, Android



Mobile Remote Control

digitalSTROM Home Apps

Visualization and notification



Email Notifications



Push Notification



Consumption Indicator



Custom States

digitalSTROM Home Apps



LED Setting DIM Wizard



dS Doku

digitalSTROM Home Apps

Automation



Timer



Custom Actions



Activity Monitoring



Scene Responder



Activity Monitoring



Auto Off



Motion Sensor



Climate Control



Ventilation Control

digitalSTROM Services



Remote Connectivity
my.digitalSTROM



IFTTT



Google Home
(only available in German)



Amazon Alexa

Integration Apps



Bosch



DoorBird



Dornbracht



Harmony



Hekatron



HUE



Netatmo



Panasonic



REHAU
Nea Smart



Siemens



Smarter



SONOS



Thanos



Tielsa



u::Lux



V-ZUG

Any questions?

Phone +41 44 445 99 67

E-Mail info@digitalstrom.com

Mo. to Fr. from 08:00 am - 05:00 pm
(normal charges for landline calls)